

## Enviro Klean® EK Restoration Cleaner Cleaning Specification

*Specifier Note: The information provided below is intended to guide the Architect in developing specifications for products manufactured by PROSOCO, Inc. and should not be viewed as a complete source of information about the product(s). The Architect should always refer to the Product Data Sheet and MSDS for additional recommendations and for safety information. See also PROSOCO Section 04900 Masonry Restoration & Cleaning.*

*Specifier Note: Paragraph below is for PART 1 GENERAL, Quality Assurance.*

### Test Area

Test a minimum 4 ft. by 4 ft. area on each type of masonry. Use manufacturer's application instructions. Let the test panel dry 3 to 7 days before inspection. Keep test panels available for comparison throughout the cleaning project.

*Specifier Note: Paragraphs below are for PART 2 PRODUCTS, Manufacturers and Products.*

**Manufacturer:** PROSOCO, Inc., 3741 Greenway Circle, Lawrence, KS 66046. Phone: (800) 255-4255; Fax: (785) 830-9797. E-mail: [CustomerCare@prosoco.com](mailto:CustomerCare@prosoco.com)

### Product Description

Enviro Klean® EK Restoration Cleaner is a concentrated gel for dissolving tough carbon deposits and other atmospheric staining. A practical alternative to conventional acidic cleaners, near-neutral pH EK Restoration Cleaner cleans brick, granite, sandstone, terra cotta, and other masonry including most limestone. Safer and less expensive than sandblasting or steam cleaning, it also loosens and dissolves dirt, paint oxidation, and other stains associated with aged and dirty buildings. It's perfect for projects where harsh acid cleaners are not allowed.

### Technical Data

FORM: Clear amber gel  
SPECIFIC GRAVITY: 1.06  
FLASH POINT: N/A  
pH: 5.5 (concentrate)  
WT./GAL.: 8.82 lbs.  
FREEZE POINT: N/D

### Limitations

- Not suitable for cleaning most concrete or marble surfaces. See Sure Klean® Limestone Restorer or Sure Klean® 766 Limestone & Masonry Prewash/Afterwash for these applications.
- Not recommended for interior use. Contact PROSOCO's Customer Care (800-255-4255) for recommendations for the most appropriate Sure Klean® or Stand Off® interior cleaning system.
- May not be suitable for some polished stone and "glazed" surfaces. Always test.
- Product may bleach certain types of light- or buff-colored masonry materials. Always test.
- May damage glass and architectural aluminum.

*Specifier Note: Paragraphs below are for PART 3 EXECUTION, Installation.*

### Application

Before applying, read "Protect" and "Precautionary Measures" sections in the Manufacturer's Product Data Sheet for EK Restoration Cleaner. Do not dilute or alter.

1. Prewet surface with fresh water.
2. Apply cleaner using a brush or roller. Gentle scrubbing application will improve results.

3. Leave the cleaning solution on the surface for 10-20 minutes. Heavy soiling or mineral deposits may require longer dwell times. Do not let cleaning solution "dry in" to the masonry. If drying occurs, lightly wet treated surfaces with fresh water, and reapply the cleaner, gently scrubbing.
4. Rinse thoroughly with fresh water.
5. Repeat steps 1-4 if necessary.

Note: Pressure rinsing equipment with 600-1000 psi and 15-30 degrees fan tip is most effective. Older, more delicate masonry may require restricting water pressure to avoid damage. Always test first.