

# **POLYGUARD 650 LT LIQUID ADHESIVE**

## **ROLLER-GRADE ADHESIVE TO PROMOTE ADHESION OF POLYGUARD WATERPROOFING MEMBRANE**

### **DESCRIPTION:**

**POLYGUARD 650 LT LIQUID ADHESIVE** is a rubber based adhesive in solvent solution which is specifically formulated to provide excellent adhesion with the **POLYGUARD WATERPROOFING MEMBRANE** under many kinds of surface conditions. **650 LT LIQUID ADHESIVE** is an integral part of the **POLYGUARD WATERPROOFING SYSTEM** and sufficient liquid adhesive must be used on dry surfaces to condition them to be dust free so that the substrate is suitable for the application of **POLYGUARD WATERPROOFING MEMBRANES**.

### **USES: 650 LT LIQUID ADHESIVE...**

- Used to prime all structural concrete, masonry, insulation, or wood surfaces on which Polyguard Waterproofing Membranes will be applied.
- Designed to be used on applications down to 25°F. (-4°C).
- May be used on horizontal surfaces, but remains tacky, and precautions must be used in this application.
- Must be used on all concrete block and brick wall conditions.

### **APPLICATION:**

**650 LT LIQUID ADHESIVE** may be applied with roller or brush. A roller with a heavy nap should be used, such to carry sufficient material to the area being primed.

Apply all **650 LT LIQUID ADHESIVE** to a clean, dry, dust free, and frost free surface at a coverage of approximately 250 to 350 square feet per gallon. The liquid adhesive should be spread sufficiently to avoid areas of excess material. Areas of excess material will lengthen the drying time on the application of the **650 LT LIQUID ADHESIVE**.

**650 LT LIQUID ADHESIVE** is to dry a minimum of 1 hour, and may dry quicker due to drying conditions.

This product is red in color and will remain tacky when dry. The application of liquid adhesive should be limited to what can be covered with **POLYGUARD WATERPROOFING MEMBRANE** in one working day. Any areas not covered with membrane during the day must be reprimed, and be sure to cover all open containers when not applying liquid adhesive.

### **SAFETY, STORAGE AND HANDLING INFORMATION:**

**POLYGUARD 650 LT LIQUID ADHESIVE** vapors are flammable. User should review Material Safety Data Sheet (MSDS) for this product and follow safety instructions listed therein.

## **PRECAUTIONS:**

**650 LT LIQUID ADHESIVES** are industrial coatings and would be harmful or fatal if swallowed. Marked as a red label flash point product, prohibit flames, sparks, welding and smoking during application. Refer to product label and Material Safety Data Sheets for handling, use and storage.

Solvents could be irritating to the eyes. In case of contact with eyes, flush with water and contact physician.

Avoid prolonged contact with skin and breathing of vapor or spray mist from liquid adhesive. If in confined areas, use adequate forced ventilation, fresh air masks, explosion proof equipment, and clean clothing. Close container after each use. Keep out of reach of children.

This material is offered for sale by **POLYGUARD PRODUCTS, INC.**, only for the expressed purposes as described in this literature. Any use of the products described in this literature for purposes other than taught therein by **POLYGUARD PRODUCTS, INC.** shall be the responsibility of the purchaser and **POLYGUARD PRODUCT, INC.** does not warrant nor will be responsible for any misuse of these products. **POLYGUARD PRODUCTS, INC.** will replace F.O.B. Ennis, Texas, material not meeting our manufacturer's specifications one year from date of sale. **POLYGUARD** products as described herein are for industrial use only. The application procedures should be performed by workmen who are skilled in the application of materials described herein in accordance with manufacturer specifications.

## **MATERIAL SAFETY DATA:**

All Material Safety Data Sheets and precautionary labels should be read and understood by all user supervisory personnel and employees before using. Consult **POLYGUARD PRODUCTS, INC.**'s Material Safety Data Sheets and OSHA regulations for additional safety and health information for the products described herein. Purchaser is responsible for complying with all applicable federal, state or local laws and regulations covering use of the product including waste disposal.

This is not a Material Safety Data Sheet and is not to be used as such. **POLYGUARD** has prepared separate Material Safety Data Sheets on each product.

## **TECHNICAL SERVICE AND AVAILABILITY:**

Technical assistance, information and **POLYGUARD** products are available through a nationwide network of distributors and architectural representatives or contact **POLYGUARD PRODUCTS, INC.**