

High Performance Intumescent Acrylic Firestop Sealant

Product Description:

TREMstop IA is a single component, water-based, intumescent acrylic firestop sealant. The intumescent property of TREMstop IA means that the material will expand to fill any void caused from combustible materials that burn during a fire. TREMstop IA is a unique, firestopping sealant that has been tested at independent laboratories to treat 95% of the applications you commonly encounter on a project. TREMstop IA also has exceptional sealant qualities, such as superb unprimed adhesion, excellent flexibility, easy gunning, and the ability to be painted once fully cured.

Tested Applications:

PENETRATIONS:

- Steel, Copper and EMT pipe
- Plastic Pipe (vented and closed)
- AB/PVC and Cellular Glass Pipe Insulation
- Romex Cables, Jacketed Cables and Bundles
- Ductwork and Blank Openings

BUILDING ASSEMBLIES:

- Concrete and CMU
- Gypsum Wallboard
- Wood Frame Construction
- Metal Pan Deck
- Insulated Pipes
- Joints

TREMCO
Sealants and Weatherproofing Division
... Helping Contractors Win Since 1928



Limitations:

- Not recommended for use in passive fire containment systems not approved by Tremco.
- Do not apply over damp or contaminated surfaces.

Packaging:

- 10.1 fl. oz. (300ml) cartridge
- 28.7 fl. oz. (850ml) cartridge
- 20.0 fl. oz. (600ml) sausages
- 5 gal. (19L) pails

Color:

Rust Red

Storage:

One (1) year from date of manufacture when stored in unopened containers in dry areas under 80°F (27°C).
Protect from freezing.

Applicable Test Standards:

- ASTM E814 (UL 1479)
- ASTM E119 (UL 263)
- CAN4-S115

Installation:

Refer to the Tremco Firestop or the UL/ULC Fire Resistance Directory for specific application instructions. The firestop system details will cover the required sealant depth, necessary amount of packing material and the permitted joint size or annular space. TREMstop IA is a gunnable sealant, typically applied using conventional caulking equipment.


Cleaning:

TREMstop IA can be removed from tools, caulking guns and installation smears with water while the sealant is still wet.

Warranty:

Tremco warrants its sealants to be free of defects in materials but makes no warranty as to appearance or color. Since methods of application and on-site conditions are beyond our control and can affect performance, Tremco makes no other warranty, expressed or implied, including warranties of MERCHANTABILITY and FITNESS FOR A PARTICULAR PURPOSE, with respect to sealants, Tremco's sole obligation shall be, at its option, to replace, or to refund the purchase price of the quantity of the sealant proved to be defective and Tremco shall not be liable for any loss or damage.

TREMstop Family of Products are Approved by:



Typical Firestopping UL/cUL/ULC Tested Systems

Penetrating Item	Concrete	Gypsum
Multi-Metal	CAJ 1448 SP 830	
Metallic Pipe	CAJ 1302 SP 831	WL 1158
Plastic Pipe	CAJ 2184 SPC 19	WL 2159
Cables	CAJ 3141 SPC 834	WL 3131
Insulated Pipe	CAJ 5121 SP 832/833	WL 5082
Vent Duct	CAJ 7044	WL 7039

Tremco Inc.
2628 Pearl Road
Medina, Ohio 44256
USA
Phone: (330) 220-7072
Fax: (330) 220-7075
Toll Free: (800) 209-2404

An **RPM** Company

TREMstopTM
Fire Protection Systems Group

For MSDS and Spec
Data Sheets, call our 24-hour
Fax-Back Line: 1-800-551-2806
or

visit our website:
www.tremcofirestop.com

Tremco Ltd.
215 Wicksteed Ave.
Toronto, Ontario M4H 1G7
Canada

Phone: (416) 421-3300
Fax: (416) 467-2448
Toll Free: (800) 263-6046

2/03 TSIA